

WENZHOU LUCHENG NDT EQUIPMENT CORP.

(LCNDT)

Film Viewer

ITEM	PICTURE	CHARACTERISTIC
<p>Strong LED Industrial X-Ray Film Viewers FV-2008</p>	 <p>CE ISO</p> <p>LCNDT®</p>	<ul style="list-style-type: none"> ◆ Luminance: $\geq 205,000 \text{ Cd/m}^2$ (643,700Lux), ◆ Uniformity: 0.9, Diffusion factor: 0.95 ◆ Viewer window: 220×80mm (8.66" × 3.15") ◆ Maximum Density: $\geq 4.3 \text{ H/D}$ ◆ Unlimited Dimmer for LED ◆ Imported LED chip with original packing ◆ Life span up to more than 50,000 hours ◆ Rugged aluminum frame ◆ Over-Temperature warning (check that the power light is red)
<p>Super Bright Industrial LED Film Viewers FV-2008 PLUS</p>	 <p>CE ISO</p> <p>LCNDT®</p>	<ul style="list-style-type: none"> ◆ Luminance : $300,000 \text{ Cd/m}^2$ (942,000Lux) ◆ Uniformity: 0.95, Diffusion factor: 0.95 ◆ Viewer window: 220×65mm (8.66" × 2.56") ◆ Maximum Density: $\geq 4.5 \text{ H/D}$ ◆ Imported LED chip with original packing ◆ Electronic Light mask - World First ◆ Low noise: Fan with temperature depended
<p>Portable LED Industrial X-Ray Film Viewers FV-2009</p>	 <p>CE ISO</p> <p>LCNDT®</p>	<ul style="list-style-type: none"> ◆ Luminance: $103,000 \text{ Cd/m}^2$ (323,420Lux) ◆ Uniformity: 0.95, Diffusion factor: 0.95 ◆ Viewer window: 200×60mm (7.87" × 2.36") ◆ Maximum Density: $\geq 4.0 \text{ H/D}$ ◆ Weight less than 2.5 Kg ◆ 12 hours continues maximum luminance, Surface temperature rise $\leq 15^\circ \text{C}$ ◆ Unlimited dimmer from 5%-100% ◆ Rugged aluminum frame, engineering plastic
<p>Intelligent LED Film Viewer + Densitometer FV-2009T</p>	 <p>CE ISO</p> <p>LCNDT®</p>	<ul style="list-style-type: none"> ◆ Portable LED film viewer combine with Densitometer ◆ High Luminance: $\geq 120,000 \text{ Cd/m}^2$ ◆ Uniformity: 0.95, Diffusion factor: 0.95 ◆ Viewer window: 200×60mm (7.87" × 2.36") ◆ Maximum Density: $\geq 4.1 \text{ H/D}$ ◆ High Accuracy: $\pm 0.02 \text{D}$ ◆ Max. Density(Densitometer): $\geq 5.0 \text{ H/D}$ ◆ Program Mode for customer calibration(patent technology) ◆ Separated design, easy for maintainece ◆ Rugged design. whole alloy aluminium

<p>Large Screen LED Industrial X-Ray Film Viewers FV-2010 Plus</p>	 <p>CE ISO</p> <p>ICNDT®</p>	<ul style="list-style-type: none"> ◆ Max. Luminance: $\geq 130,000 \text{Cd/m}^2$ (408,200Lux) ◆ Uniformity: 0.95, Diffusion factor: 0.95 ◆ Large viewer window: 400×100mm (15.75" ×3.94"), 400×85mm(15.75" ×3.35") are available ◆ Maximum Density: ≥ 4.2 H/D ◆ Electronic Light mask - World First ◆ Low noise: Fan with temperature depended
<p>Portable 4.5x17" screen LED Film Viewers + Densitometer FV-2010T PLUS</p>	 <p>CE ISO</p> <p>ICNDT®</p>	<ul style="list-style-type: none"> ◆ Max. Luminance: $\geq 130,000 \text{Cd/m}^2$ (408,200Lux) ◆ Uniformity: 0.95, Diffusion factor: 0.95 ◆ Large viewer window: 400×100mm (15.75" ×3.94") ◆ Maximum Density: ≥ 4.2 H/D ◆ Densitometer High Accuracy: $\pm 0.02D$ ◆ Max. Density(Densitometer): ≥ 5.0 H/D ◆ Electronic Light mask - World First ◆ Low noise: Fan with temperature depended
<p>Smart Handy LED Film Viewer FV-2013</p>	 <p>CE ISO</p> <p>ICNDT®</p>	<ul style="list-style-type: none"> ◆ Superb Portable, Single-Hand Operation, Li Battery Powered, Overall Weight Only 1kg ◆ Max. Luminance $> 110,000 \text{Cd/m}^2$ ◆ Uniformity: 0.95, Diffusion factor: 0.95 ◆ Viewer window: 150×45mm (5.90" ×1.77") ◆ Maximum Density: ≥ 4.0 H/D ◆ Waterproof Protection IP55, Viewing Wet Film Directly ◆ Intelligent Auto-Temperature Control System, Over-Temperature Protection
<p>14×17 inch Industrial X Ray LED film viewer FV-2014</p>	 <p>CE ISO</p> <p>ICNDT®</p>	<ul style="list-style-type: none"> ◆ 16.1" × 13"(335×410mm) window size (fit 17" × 14" film) ◆ Max. Luminance: $\geq 82,800 \text{Cd/m}^2$ (260,000Lux) ◆ Uniformity: 0.95, Diffusion factor: 0.95 ◆ Maximum Density: ≥ 3.8 H/D ◆ Electronic light mask in vertical and horizontal - World First ◆ Rugged viewer feet, support any angle and wall mount ◆ Smart cooling system, Fan with temperature depended
<p>All the products enjoy 2 years free service guarantee</p>		